	• <u>V</u> ie	w E	14246 upper surface dit <u>I</u> ools <u>W</u> indow		aligned.w	\$p: I				_ <u>_</u>
ם [נ	ŝ 5		太真图 8 红	. HA						
1			((((leadframe lead adj		Ĺ	$\exists $	Search List Browse Queue Clear	E 4		
			29) (Land, contact elect (stack\$4 near2 ((micro			- 1	DBs USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	٠	.	
ī			(stack)4 nearz ((micro 3) (Jead contact electi			- }			Plurals	
i-			stack\$4 near2 ((micro				Default operator: OR	₽	Highlight all hit tern	ns init
1 j-			((lead contact electr			- 1	((((leadframe lead adj frame)			
(microchip micro adj chip chip integrate) with ((microchip micro adj chip chip integrated adj circuit die ic semiconductor adj (device element			
1			stack\$4 near2 ((micro				structure))			
** (43) insulat\$4 near2 cover\$4 near4 exposed adj2 (contact eliging (828) insulat\$4 near4 exposed adj2 (contact electrode lead)) with ((encapsula\$3 encapsulation mold\$3 resin))) and ((1 adj shaped) near2 ((leadframe lead adj frame lead)))) ((((stack\$4 near ((microchip micro adj chip chip integrated adj circuit die ic semiconductor adj (device			
			prevent\$3 reduc\$3 elin				element structure)))) (stack\$4 near packag\$3)) and (((leadframe le	ad adj frame))	with ((encapsula\$3	}
1			microchip micro adj cl	hip chip integrated ad	lj circuit di	Ш	encapsulation mold\$3 resin)) with ((microchip micro adj chip chip in semiconductor adj (device element structure))))) and ((offset stag	ntegrated adj cir	rcuit die ic	~~?
i			6177139"			Ш	angle pitch oblique\$4 inclin\$4 displac\$3))	Reido aimedo vi	Rraght mighthe me	aız
 	rave		((((leadframe lead adj	frame) U		Ш	• • • • • • • • • • • • • • • • • • • •			
	Tag					Ш	1 2 500)		
		KUUL.	31)			111				
					*	- 11	\mathbf{A}	>		
$ \mathfrak{D} $	UDO	;			į		April 0 003	•		
(S)		i ie				- -	Aprilous	· · · · · · · · · · · · · · · · · · ·	<u> </u>	7.3 · · ·
(S)	UDC Que	i ie			<u>.</u>	<u> </u>	め BRS f あ ISLR 図 Image 関 Text	· · · · · · · · · · · · · · · · · · ·		7-3 11
Ø 3	UDC Que Tras	i ie		 Document ID	Issue Date		Title	Current OR	Current XRef	Re
S	UDC Que Tras	ue h	Asada, Junichi et al.	US 5665651 A	Issue Date			29/827	Current XRef 257/E21.504; 257/E23.042:	Re
S) B)	UDC Quer Tras	ue h	Asada, Junichi et al. Fujimoto, Hiroaki et	US 5665651 A	Issue Date		Title	29/827	257/E21.504;	Re
S	UDC Quer Tras	h	Asada, Junichi et al. Fujimoto, Hiroaki et al.	US 5665651 A US 6498393 B2	Issue Date 19970909 20021224	13 34	Title Process for encapsulating a semiconductor device and lead frame Semiconductor device and method for the fabrication thereof	29/827 257/692	257/E21.504; 257/E23.042;	Re
S) B)	UDC Quer Tras	h	Asada, Junichi et al. Fujimoto, Hiroaki et al.	US 5665651 A US 6498393 B2	Issue Date 19970909 20021224	13	Title Process for encapsulating a semiconductor device and lead frame	29/827 257/692	257/E21.504; 257/E23.042; 257/666;	Re
S	UDC Quer Tras	h V	Asada, Junichi et al. Fujimoto, Hiroaki et al. Horiuchi, Michio et	US 5665651 A US 6498393 B2 US 20020031867 A1	Issue Date 19970909 20021224 20020314	13 34 17	Title Process for encapsulating a semiconductor device and lead frame Semiconductor device and method for the fabrication thereof	29/827 257/692 438/125	257/E21.504; 257/E23.042; 257/666;	Re
S	UDC Quer Tras	h D D D D D D D D D D D D D	Asada, Junichi et al. Fujimoto, Hiroaki et al. Horiuchi, Michio et al.	US 5665651 A US 6498393 B2 US 20020031867 A1 US 20020027273 A1	Issue Date 19970909 20021224 20020314 20020307	13 34 17	Title Process for encapsulating a semiconductor device and lead frame Semiconductor device and method for the fabrication thereof Semiconductor device and process of production of same Semiconductor package and fabricating method thereof	29/827 257/692 438/125 257/678	257/E21.504; 257/E23.042; 257/666; 257/787;	Re
S) S)	UDC Quer Tras	h V	Asada, Junichi et al. Fujimoto, Hiroaki et al. Horiuchi, Michio et al.	US 5665651 A US 6498393 B2 US 20020031867 A1	Issue Date 19970909 20021224 20020314	13 34 17	Title Process for encapsulating a semiconductor device and lead frame Semiconductor device and method for the fabrication thereof Semiconductor device and process of production of same Semiconductor package and fabricating method thereof Lead frame structure of resin sealed semiconductor package e.g. chip	29/827 257/692 438/125 257/678	257/E21.504; 257/E23.042; 257/666; 257/787;	Re
(A) (B) (B) (B) (B) (B) (B) (B) (B) (B) (B	Quei Tras	No.	Asada, Junichi et al. Fujimoto, Hiroaki et al. Horiuchi, Michio et al.	US 5665651 A US 6498393 B2 US 20020031867 A1 US 20020027273 A1	Issue Date 19970909 20021224 20020314 20020307	13 34 17 12 7	Title Process for encapsulating a semiconductor device and lead frame Semiconductor device and method for the fabrication thereof Semiconductor device and process of production of same Semiconductor package and fabricating method thereof Lead frame structure of resin sealed semiconductor package e.g. chip size package, has protruding portion of L shaped lead frame acting as	29/827 257/692 438/125 257/678	257/E21.504; 257/E23.042; 257/666; 257/787;	Re
S	UDC Quer Tras	h D D D D D D D D D D D D D	Asada, Junichi et al. Fujimoto, Hiroaki et al. Honuchi, Michio et al. Huang, Chien Ping	US 5665651 A US 6498393 B2 US 20020031867 A1 US 20020027273 A1 JP 2000077598 A JP 11340373 A	20021224 20020314 20020307 20000314 19991210	13 34 17 12 7	Title Process for encapsulating a semiconductor device and lead frame Semiconductor device and method for the fabrication thereof Semiconductor device and process of production of same Semiconductor package and fabricating method thereof Lead frame structure of resin sealed semiconductor package e.g. chip size package, has protruding portion of L shaped lead frame acting as Thin small sized resin sealed electronic circuit chip has L shaped	29/827 257/692 438/125 257/678	257/E21.504; 257/E23.042; 257/666; 257/787;	Re
(A) (B) (B) (B) (B) (B) (B) (B) (B) (B) (B	Quei Tras	No.	Asada, Junichi et al. Fujimoto, Hiroaki et al. Honuchi, Michio et al. Huang, Chien Ping	US 5665651 A US 6498393 B2 US 20020031867 A1 US 20020027273 A1 JP 2000077598 A	20021224 20020314 20020307 20000314 19991210	13 34 17 12 7	Title Process for encapsulating a semiconductor device and lead frame Semiconductor device and method for the fabrication thereof Semiconductor device and process of production of same Semiconductor package and fabricating method thereof Lead frame structure of resin sealed semiconductor package e.g. chip size package, has protruding portion of L shaped lead frame acting as	29/827 257/692 438/125 257/678	257/E21.504; 257/E23.042; 257/666; 257/787;	Re
(A)	UDC Quee Trass		Asada, Junichi et al. Fujimoto, Hiroaki et al. Horiuchi, Michio et al. Huang, Chien Ping Abe, Shunichi et al.	US 5665651 A US 6498393 B2 US 20020031867 A1 US 20020027273 A1 JP 2000077598 A JP 11340373 A US 20020105061 A1	20020314 20020314 20020307 20020307 20000314 19991210 20020808	13 34 17 12 7 7	Title Process for encapsulating a semiconductor device and lead frame Semiconductor device and method for the fabrication thereof Semiconductor device and process of production of same Semiconductor package and fabricating method thereof Lead frame structure of resin sealed semiconductor package e.g. chip size package, has protruding portion of L shaped lead frame acting as Thin small sized resin sealed electronic circuit chip has L shaped metal lead frame with larger shape than chip and is depressed from or Semiconductor device and manufacturing method thereof	29/827 257/692 438/125 257/678	257/E21.504; 257/E23.042; 257/666; 257/787; 438/106	Re
(A)	VIDO Quer Tras	E E	Asada, Junichi et al. Fujimoto, Hiroaki et al. Honuchi, Michio et al. Huang, Chien Ping	US 5665651 A US 6498393 B2 US 20020031867 A1 US 20020027273 A1 JP 2000077598 A JP 11340373 A US 20020105061 A1	20020314 20020314 20020307 20020307 20000314 19991210 20020808	13 34 17 12 7 7	Title Process for encapsulating a semiconductor device and lead frame Semiconductor device and method for the fabrication thereof Semiconductor device and process of production of same Semiconductor package and fabricating method thereof Lead frame structure of resin sealed semiconductor package e.g. chip size package, has protruding portion of L shaped lead frame acting as Thin small sized resin sealed electronic circuit chip has L shaped metal lead frame with larger shape than chip and is depressed from or	29/827 257/692 438/125 257/678 257/666 206/716	257/E21.504; 257/E23.042; 257/666; 257/787;	Re

.